

Subsurface Safety Valve

Tubing Retrievable Surface Controlled Subsurface Safety Valve w/thru-the-flapper self-equalizing feature.

Item No	Description	Quantity pcs	Unit Price EUR /pcs	Price required quantity EUR excl.VAT
1	Tubing Retrievable Surface Controlled Subsurface Safety Valve w/thru-the-flapper self-equalizing feature, Size 3 1/2" x 2.812" min. ID w/ 5.700 " OD, working Pressure 5000 PSI, working temperature 200-300 °F, w/ material 9Cr1Mo on flow path, w/ X (Halliburton Style) top no-go profile, API 14A Verified; w/ 3 1/2" 9.2# VAGT Top x Bottom thread.	4		0,00
2	Technical manual with description of the subsurface safety valve including drawing for the item 1.	1		0,00
3	Control Line 1/4" x 0.049" ID w/ 7350 PSI Working Pressure, Material 316SS Welded and Drawn; 150ft per Reel.	4		0,00
4	Control Banding Straps Size 3/4" Material Steel w/32" lenght fit to 3 1/2" Tubing	50		0,00
5	Clamps suitable to attach of control line to 3 1/2" tubing	40		0,00
6	Hydraulic Oil AERO HF 585B Castrol (60 Liters)	1		0,00
Total price				0,00